

THE PRIORY DOOR GROUP LIMITED
Leading Specialists in Doors to the Trade



Lionel Works
89/91 Rolfe Street
Smethwick
West Midlands
B66 2AY

T | 0121 558 6406
F | 0121 555 7140
e | sales@priory-group.co.uk
www.priory-group.co.uk



**Single Phase Tube Motor Operated Roller Shutter
Door - (DOC) Declaration of Conformity, (DOP)
Declaration of Performance, Door Safety, Operation,
Maintenance and Installation Instructions**

TITAN



Lionel Works
89/91 Rolfe Street
Smethwick
West Midlands
B66 2AY

T | 0121 558 6406
F | 0121 555 7140
e | sales@priory-group.co.uk
www.priory-group.co.uk

CE MARKED – Machinery Directive 2006 / 42 / EC
UKCA MARKED – Supply of Machinery (Safety) Regulations

DECLARATION OF CONFORMITY

Machine description Rolling Shutter Door
Make Industrial Rolling Shutter
Year of Manufacture _____
Serial number _____
Manufacturer The Priory Shutter & Door Co. Ltd.

Is in conformity with the provision of the above EC directive and Supply of Machinery (Safety) Regulations

Testing undertaken at Warrington A.P.T. Laboratories Ltd.
Test report number 145643 and 146755a

The company above declares under its own authority that the above system is fully compliant with: -

- 2006/42/EC – Machinery Directive

The company additionally declares under its own authority that the system is in full compliance with the following directives: -

- 2014/30/EU – Electro-magnetic Compatibility Directive
- 2014/53/EU – Radio Equipment Directive

The company above declares under its own authority that the above system is fully compliant with: -

- Supply of Machinery Regulations 2008

The company additionally declares under its own authority that the system is in full compliance with the following directives: -

- Electromagnetic Compatibility Regulations 2016
- Radio Equipment Regulations 2017

The equipment above must not be put into service until the machinery into which it is to be incorporated has been declared in conformity with the provisions of the directive.

Signed _____
Date 02/12/2024
Name Gavin Cooper
Position Managing Director



Lionel Works
89/91 Rolfe Street
Smethwick
West Midlands
B66 2AY

T | 0121 558 6406
F | 0121 555 7140
e | sales@priory-group.co.uk
www.priory-group.co.uk

CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE
No. 0004 CPR DoP 04-2013

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified below: -

1. Manufacturer: **The Priory Shutter & Door Co Ltd. 89-91 Rolfe Street, Smethwick, West Midlands, B66 2AY**
2. Type, Batch and or Serial number: _____
3. Identification code: **Tube Motor Rolling Shutter, (Titan Range)**
Single phase electrically Operated
4. Intended Uses: **External/Internal Door For Vehicle and/or Pedestrian Access**
5. Notified body and tasks: **Exova Warrington APT, a UKAS accredited Testing Laboratory (No. 0621) and EC Notified Body number (No, 1104). Key Industrial Park, Fernside Road, Willenhall, West Midlands, WV13 3YA, performed initial type tests under system 3 and issued test report No's; 145643/1, 145643/2, 145643/3, 145643/4, 146755A & 329811A**
6. Assessment and verification of constancy of performance: **AVCP System 3**
7. European Technical Assessment: **Not Applicable**

8. Declared performance

Essential Characteristics	Declared Performance	Harmonised Standard
Water Tightness	N.P.D.	EN 13241-1:2003 + A2:2016
Dangerous Substances	None	
Resistance To Wind Load	Class +5/-5	
Thermal Transmittance	N.P.D.	
Air Permeability	N.P.D.	
Safe Opening	Pass	
Definition of geometry of glass components	N.P.D.	
Mechanical resistance and stability	Pass	
Operating Forces	Pass	
Durability of Water Tightness, Thermal Resistance and Air Permeability against degradation	N.P.D.	

Specific Technical Documentation: **Not Applicable**

9. The performance of the product identified above is in full conformity with the declared performances.
This declaration of performance is issued under the sole responsibility of the company identified above

Signed _____
Date 02/12/2024
Name Gavin Cooper
Position Managing Director



ROLLER SHUTTER DOOR SAFETY INSTRUCTIONS

THE FOLLOWING SAFETY INSTRUCTIONS MUST BE ADHERED TO AT ALL TIMES.

FAILURE TO DO SO COULD RESULT IN AN ACCIDENT/INJURY.

1. Keep openings clear of any obstructions.
2. Do not lean anything against the door curtain, guides, roller barrel assembly or coil casing.
3. Do not walk under a door whilst operating. Wait until the door is fully open.
4. Do not "rush" through a door that is closing. Wait for the door to fully close, and then re-open.
5. Do not operate a damaged door. If damaged, contact a service engineer immediately.
6. If the door becomes difficult to operate; cease using and contact a service engineer immediately.
7. Only use opening and closing equipment supplied with the door.
8. Do not suspend/anchor anything from the roller shutter.
9. Do not use the door to lift materials/personnel.
10. Do not remove the coil casing (if supplied) around the roller barrel assembly unless the door is stopped, the haul chain is secured and locked in position or the power is switched off at the isolator on electrically operated doors.
11. Do not force any form of locking.
12. In the event of a power failure, it is possible to manually lift the door to the open position or close the door as follows: -

When using a high level override system always gain access in a safe manner.

ALWAYS isolate the power supply before using the manual override.

- Locate the eye assembly projecting below the motor.
- Use the removable crank handle supplied with the shutter, fit this to the eye assembly and wind the door in the appropriate direction to operate the shutter.
- On larger doors, it may be necessary to pull the hand crank down until a click is heard prior to winding the door up or down. Once completed, push the hand crank until the click is heard again which enables the power operation once the supply is re-established.
- Always watch the door to ensure it is moving in the direction intended. Operating the door beyond its intended final limit position may damage the motor.

IMPORTANT

Any work carried out on the electrical components of the roller shutter door must be by a qualified electrician, who must ensure the equipment is isolated prior to commencing any work.

Roller shutter doors must not be modified from their original design. If future modifications are required, the manufacturer must be consulted.

Locking mechanisms on electrically operated roller shutter doors are not recommended unless used in conjunction with an interlock switch which disengages the power whilst the door is in the locked position.



ROLLER SHUTTER DOOR OPERATING & MAINTENANCE

Single Phase Tubular Motor Operated Roller Shutter Doors

Tube motor operated roller shutter doors are designed for low usage openings, heavy usage (more than 3 operations per hour) will significantly reduce the life of the motor and will invalidate the warranty.

Tube motor doors are supplied with an independent safety brake device that is installed at the opposite side to the motor which engages and locks the barrel assembly in position should the door “drop” due to the unlikely event of a single component failure that would exceed the maximum allowed RPM of the brake assembly.

Various control options are available for this type of motor and installation/commissioning of these should be in conjunction with the relevant installation instructions supplied.

a. To Open

Release all forms of locking if supplied and place into the interlock box provided.

Press the “Open” or “Up” button on the rocker switch or turn the key within the key switch. The door will automatically stop at the top when it reaches its pre-set limit.

b. To Close

Press the “Close” or “Down” button on the rocker switch or turn the key within the key switch. The door will automatically stop at the bottom when it reaches its pre-set limit.

Remove the locking from the interlock box and re-fit to the door if supplied.

c. To Stop

Press the red stop button on the starter unit/control panel.

IMPORTANT: Electrically operated doors should only be wired in by fully experienced and competent electricians

On ALL power operated doors, manual operation is prohibited whilst the motor is in use and could cause serious damage to the operator.

Service and Maintenance

Like any other machinery, roller shutter doors require regular service and maintenance to ensure that they are working correctly and as designed.

Not all defects will have an immediate effect on the safety and operation of your door, but it will prove more cost effective to repair any defect earlier than risk a larger more costly repair at a later date.

Your roller shutter door will last many years with regular servicing and maintenance, but all components will wear and deteriorate over a period of time.

We recommend that your roller shutter doors are serviced at least once per year but recommend more frequent service visits if the doors are operated regularly.

Up to 10 operations per day – 1 visit every 6 months

Up to 30 operations per day – 1 visit every 3 months

Over 30 operations per day – 1 visit every 2 months

We recommend that you carry out your own daily inspection of your roller shutter doors, with some simple checks as follows: -

1. There is no damage to any parts of the door – Any damage to the door needs to be reported and suitable action taken to ensure the door works correctly.
2. The door operates freely and does not require excessive force to operate.
3. The door remains free from dust, dirt and grime build up which could affect the operation of the door, particularly in the guides. It is not recommended to use thick grease as this hardens over time and retains debris.



ROLLER SHUTTER DOOR INSTALLATION INSTRUCTIONS

READ THESE INSTRUCTIONS FULLY BEFORE COMMENCING INSTALLATION.

1. **Check for correct:**
 - Opening details in relation to those against the job specific drawing.
 - Materials and specification as per the delivery note/checklist.
 - Structure is square and fixing faces are in line, even and free from obstructions.
 - Structure can carry the weight of the roller shutter door supplied (identified on spec. sheet attached to dwg.).
2. **Face fixing arrangement:** position the 50 mm leg of the continuous flag post angles against the structure in accordance with the dimensions and arrangement on the drawing. Mark out the fixing holes and drill the structure for the specified/supplied fixing type.
3. **Between fixing arrangement:** position the 50 mm leg of the continuous between wall angles against the reveals of the structure in order to create a fixing face with the adjacent 100 mm leg. Mark out and drill the structure for the specified/supplied fixings. Position the 50 mm leg of the continuous flag post angles against the 100 mm leg of the between wall angles in accordance with the detail on the drawing. Mark out the fixing holes and drill the 100 mm leg of the between wall angle for the specified/supplied fixings. Note – between wall angles are intentionally left un-drilled so that if the reveal is “running out” the roller shutter flag posts can still be fitted vertical.
4. Secure the end-plates to the 75 mm leg of the flag post angles at high level, using the M10 domed head fixings supplied, ensuring that the orientation for motor handing matches that of the drawing.
5. When angles are secured, use a spirit level and measure to check that;
 - The angles are square and vertical and also level horizontally across the top of the end-plates.
 - The dimension between the end-plates is correct, i.e. pin length.
6. Fit the safety brake mechanism to the plain end keyed shaft on the barrel assembly using the counter-sunk bolt and washer provided, ensuring that the brake will lock on inertia when rotated in the **downward** direction. Slide the telescopic keyed shaft into the barrel, reducing the overall pin length to enable fitting between plates.
7. Remove the pin from the protruding stub at the head of the motor and using suitable lifting equipment, lift the barrel assembly and offer into the “star bracket” on the inside of the motor end plate. Rotate the barrel and position allowing the limits/manual over-ride to face the floor. Fit the pin back in the stub, retaining the motor head within the star bracket.
8. Slide the telescopic keyed shaft back out to the correct position and offer the safety brake over the mounting plate on the inside of the dummy end plate. Lock the shaft in position with the grub screw on the collar. Bolt the safety brake to the end-plate using the M8 x 40 nuts & bolts provided.
9. Slide the hexagonal manual over-ride shaft through the head of the motor and secure with screw & washer, allowing the extended shaft to point towards the floor. Fit the manual over-ride eye to the shaft with the split pin (provided).
10. Connect a test lead and run the door down to the bottom limit.



ROLLER SHUTTER DOOR INSTALLATION INSTRUCTIONS

11. Secure the top section of the curtain to the barrel using the top continuous slotted lath and M10 nuts and washers provided. If the door is internally fitted then the curtain should be fitted “standard coil” with the concave face of the lath against the barrel assembly. If the door is externally fitted then the curtain should be fitted “reverse coil” with the convex face of the lath against the barrel assembly. Once complete, fit black plastic cover caps (provided) over the M10 nuts to protect the first “wrap”.
12. Twist back an end-lock at the bottom of the curtain section and slide into place the next section of curtain. Repeat this process until all sections are in place and the bottom rail section is fitted last. Ensure that all end-locks are twisted back into their **correct** position and that all sections follow the relevant “standard coil” or “reverse coil” pattern.
13. Fit the guide channels to the flag post angles using the M8 domed head fixings provided. Apply grease to the full height of the inside of the guide channels to facilitate smooth running. Check that the curtain operates freely within the guides.
14. Using the test switch, operate the door to set the top limit. Then close the door to set the bottom limit. Follow the motor manufacturer’s instructions closely (provided) when setting the limits.
15. If supplied, fit the hood to the end-plate cleats using the pop rivets provided. Hoods over 3000 mm in length will be supplied in multiple telescopic sections labelled “small” and “large”. Measure the overall end-plate width prior to pop riveting the telescopic sections together to ensure an accurate fit. Make a cut out in the canopy on the underside at the motor end to accommodate the manual over-ride eye.
16. Fit all the appropriate labels provided and complete the details on the “CE” badge to comply with the machinery directive. The customer must also be informed of any residual Health and Safety Risks.
17. The door can now be wired in by a competent electrician utilising the actuation equipment provided. All wiring diagrams are provided within the actuation/control enclosures – if in doubt, ask.

Tick off the checklist below (where applicable) as each test is carried out.

Guides Vertical	
Tension Correct	
Lock Operational	
Canopy Level	

Barrel Level	
Curtain Operates Freely	
Gear Alignment	
Barrel Retaining Bolt and Split Pin Fitted	

Sign and date the bottom of this page and put your name in capitals below, if this is to be the retained record of installation.



ROLLER SHUTTER DOOR INSTALLATION DIAGRAM

Single Phase Tubular Motor Operated Roller Shutter Doors

DIAGRAM 3A

